

SOLID OAK FLOORING QUALITY DESCRIPTION

TECHNICAL PARAMETERS	Tongue & groove and bevels all 4 sides. Surface could be brushed, weathered, oiled, or lacquered. For indoor use only.	
WOOD SPECIES	European Oak (Quercus petraea)	
DIMENSIONS	Thickness:	20 mm
	Width:	180 mm
	Mixed lengths:	≥ 80% 1400-2400 mm, ≤ 20% iki 1400 mm
	Allowed tolerances: Width ± 0.6 mm Lipping (between elements) ± 0.3 mm Relative wood humidity (RH) in stock 8% ±	± 3%
GRADE		
RUSTIC	 Allowed characteristics: Sound or cracked filled knots Ø u Filled knotholes Ø up to 35 mm Filled cracks Occasional sapwood or heartwood Changes in wood grain 	

Woodworm, mechanical defects, and mold are not allowed.



<u>The knot filler</u> changes colour when oiled. It absorbs the oil and pigment and adapts to the colour of the flooring. However, the knot filler does not change colour when lacquered.

COLOUR

Due to natural changes in wood grain and chemical structure, the colour of the product may differ slightly from the showroom samples.

We will not take responsibility for the flooring defects which occur due to incorrect storage, installation, maintenance, or other factors which are not caused by the producer.

UAB Brolis Timber Company code 301150664 VAT number LT100003508410 Inžinieriu st. 2, LT-54464 Sergeičikai I k., Karmėlavos sen., Kauno r. (Kauno LEZ) Lithuania www.brolistimber.eu